

# CONTROLLERS - Selection Guide

## COST EFFECTIVE FAMILIES (Temperature, PID PWM Output)

## ADVANCED FEATURES FAMILIES (Universal Input, RS485 Modbus, Ramp & Soaks, PID Analog Output, 4-20 mA retransmission, Digital Input, Square Root)



	N1030	N1030T	N1040	N1040T	N1020	N480D	N1050	N960	N120	N1200	N1200-HC	N20K48	N2000	N2000-S	N3000	
Controller Type	Temperature	Temperature	Temperature	Temperature	Temperature	Temperature	Temperature	Temperature	Process	Process	Process	Process	Process	Process	Process	
PID Output Control Mode	PWM	PWM	PWM	PWM	PWM	PWM & Analog (Optional)	PWM & Analog (Optional)	PWM & Analog (Optional)	PWM	PWM & Analog	PWM & Analog	PWM & Analog (Optional)	PWM & Analog	PWM & Analog	PWM & Analog (Optional)	
Auto Tune PID	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	
Self-Adaptive PID					✓				✓	✓	✓	✓				
Control Loops	1	1	1	1	1	1	1	1	2	1	2	1	1	1	1	
Control Action	Heat or Cool	Heat or Cool	Heat or Cool	Heat or Cool	Heat or Cool	Heat or Cool	Heat or Cool	Heat or Cool	Heat & Cool with Overlap	Heat or Cool	Heat & Cool with Overlap	Heat or Cool	Heat or Cool	Servo	Heat or Cool	
Relay Output	1	1	Up to 3	Up to 3	1	Up to 3	Up to 3	2	2	Up to 3	Up to 3	Up to 9*	Up to 4	Up to 4	Up to 4	
Pulse Output	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	Up to 25*	✓	✓	✓	
Analog Output			Optional			Optional	Optional	✓		✓	✓	Up to 8*	✓	✓	✓	
Ramp to Soak Function					✓	✓	✓	✓				✓				
Ramp & Soak Programs/Segments						1 program 9 segments	5 programs 4 segments	1 program 9 segments	20 programs 9 segments	20 programs 9 segments	20 programs 9 segments		7 programs 7 segments	7 programs 7 segments	7 programs 7 segments	
Soft-Start Function			✓	✓	✓		✓		✓	✓	✓	✓	✓	✓	✓	
Bumpless Function							✓		✓	✓	✓	✓	✓	✓	✓	
Manual Operation							✓		✓	✓	✓	✓	✓	✓	✓	
Display	Double	Double	Double	Double	Single	Double	Double	Double	Double	Double	Double	Double	Double	Double	Double	
Input Type	J, K, T, and Pt100				J, K, T, R, S, E, N, Pt100 and 0-50 mV	J, K, T, R, S, E, N and Pt100	J, K, T, S and Pt100	J, K, T, R, S, E, N and Pt100	J, K, T, R, S, E, B, N, Pt100, 4-20 mA, 0-50 mV, 0-5 V and 0-10 V	J, K, T, R, S, E, B, N, Pt100, 4-20 mA, 0-50 mV, 0-5 V and 0-10 V		J, K, T, R, S, E, B, N, Pt100, 0-20 mA, 4-20 mA, 0-50 mV, 0-5 V and 0-10 V	J, K, T, R, S, E, B, N, Pt100, 4-20 mA, 0-50 mV and 0-5 V	J, K, T, R, S, N, Pt100, 4-20 mA, 0-50 mV and 0-5 V	J, K, T, R, S, E, B, N, Pt100, 4-20 mA, 0-50 mV and 0-5 V	
Input Resolution Levels	32767	32767	32767	32767	32767	32767	32767	32767	32767	32767	32767	32767	32767	20000	32767	
Input Sample Rate	5 sps	5 sps	10 sps	10 sps	55 sps	55 sps	10 sps	55 sps	55 sps	55 sps	55 sps	55 sps	10 sps	5 sps	10 sps	
Detection Sensor Break	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	
Detection PID Loop Break			✓	✓	✓		✓		✓	✓	✓	✓			✓	
Detection Heater Break																
Alarm Number	1	1	2	2	2	2	2	2	2	Optional		4	4	2	4	
Alarm Types	Low, High, Dif, DifLo, DifHi and InputErr				Low, High, Dif, DifLo, DifHi, Ton, TEnd and InputErr	Low, High, Dif, DifLo, DifHi, EndSoak, Event and InputErr	Low, High, Dif, DifLo, DifHi, Event and InputErr	Low, High, Dif, DifLo, DifHi, EndSoak, Event and InputErr	Low, High, Dif, DifLo, DifHi, Event and InputErr	Low, High, Dif, DifLo, DifHi, ResistFail, Event and Input Error		Low, High, Dif, DifLo, DifHi, EndSoak, Event and InputErr	Low, High, Dif, DifLo, DifHi, Event and InputErr	Low, High, Dif, DifLo, DifHi, ResistFail, Event and Input Error	Low, High, Dif, DifLo, DifHi, Event and InputErr	
Digital Input									✓	✓	✓	Up to 24*	✓	✓	✓	
Remote Setpoint Input									✓	✓	✓	✓	✓	✓	✓	
Setpoint Retransmission										✓	✓	✓	✓	✓	✓	
Square Root										✓	✓	✓	✓	✓	✓	
Timer		✓		✓	✓		✓					✓				
Data Logger Function									Optional							
Password Protection	✓	✓	✓	✓	✓		✓		✓	✓	✓	✓	✓	✓	✓	
Auxiliary 24V Power Supply									✓	✓	✓	✓	✓	✓	✓	
RS485 Modbus RTU			Optional		Optional		Optional		✓	Optional	Optional	Optional	Optional	Optional	Optional	
Bluetooth												✓				
USB			✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	
CE Certification	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	
UL Certification	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	
Frontal IP65	✓	✓	✓	✓	✓	✓	✓	✓	n/a	✓	✓	✓	✓	✓	✓	
Power Supply	100-240 Vac/dc or 12-24 Vdc (Optional)								100-240 Vac/dc	100-240 Vac/dc or 12-24 Vdc (Optional)						
Panel Format	48 x 48 DIN 1/16	48 x 48 DIN 1/16	48 x 48 DIN 1/16	48 x 48 DIN 1/16	48 x 24 DIN 1/32	48 x 48 DIN 1/16	48 x 48 DIN 1/16	96 x 96 DIN 1/4	Board only Dual Display	48 x 48 DIN 1/16	48 x 48 DIN 1/16	48 x 48 DIN 1/16	96x48 DIN 1/8	96x48 DIN 1/8	96 x 96 DIN 1/4	

\*Using the micromodules